






Roofing

Nailing Schedule For Roofing

Type of Roofing	Shingles Per Square	Length of Nail	Nails Per Square	Pounds Per Square (approximate)		Labor Hours Per Square
				12 Ga. By 7/16" Head		
Roll Roofing on new roof	-	1"	252	.73	1.12	1
Roll Roofing over old roofing	-	1 3/4"	252	1.43	1.78	1 1/4
19" Selvage over old shingles	-	1 1/4"	181	1.83	1.07	1
3 Tab Sq. Butt on new roof	80	1 1/4"	336	1.22	1.44	1 1/2
3 Tab Sq. Butt Re-roofing	80	1 3/4"	504	2.38	3.01	1 3/8

Shingles

Product	Configuration	Per Square - 10' x 10'			Size		Exposure	Underwriters Laboratories Listing
		Approximate Shipping Weight	Shingles	Bundles	Width	Length		
 <p>Self-sealing random - tab strip shingle</p> <p>Multi-thickness</p>	Various edge, surface texture and application treatments	240# to 360#	64 to 90	3, 4 or 5	11 1/2" to 14"	36" to 40"	4" to 6"	A or C - Many wind resistant
 <p>Self-sealing random - tab strip shingle</p> <p>Single-thickness</p>	Various edge, surface texture and application treatments	240# to 300#	65 to 80	3 or 4	12" to 13 1/4"	36" to 40"	5" to 5 5/8"	A or C - Many wind resistant
 <p>Self-sealing square - tab strip shingle</p> <p>Three-tab</p>	Two-tab or Four-tab	215# to 325#	65 to 80	3 or 4	12" to 13 1/4"	36" to 40"	5" to 5 5/8"	A or C - All wind resistant
	Three-tab	215# to 300#	65 to 80	3 or 4	12" to 13 1/4"	36" to 40"	5" to 5 5/8"	
 <p>Self-sealing square - tab strip shingle</p> <p>No-cutout</p>	Various edge, surface texture treatments	215# to 290#	65 to 81	3 or 4	12" to 13 1/4"	36" to 40"	5" to 5 5/8"	A or C - All wind resistant
 <p>Individual interlocking shingle</p> <p>Basic design</p>	Several design variations	180# to 250#	72 to 120	3 or 4	18" to 22 1/4"	20" to 22 1/2"	-	A or C - Many wind resistant

Publisher is not liable for errors or omissions in this book. Always check your local building codes.