

# Compounds & Textures

## Joint Systems

Product	Package Size	Coverage
<b>Bedding Compound</b> Adheres tape to joints. First coat coverage for nails and corner bead.	25 lb. bags	15-20 lbs. Per 1000 sq. ft.
<b>Topping</b> For second and third coats over Bedding Compound. Used only for finishing applications.	25 lb. bags	40-45 lbs. Per 1000 sq. ft.
<b>Multi-Purpose</b> Vinyl/polymer binder multi-purpose joint product. Used for taping, finishing and texturing.	25 lb. bags	60 lbs. Per 1000 sq. ft. for joints: 15-50 lbs. Per 1000 sq. ft. for texturing.
<b>All Purpose</b> Used for bedding tape, finishing joints, filling corner bead, spotting, texturing.	25 lb. bags	60 lbs. Per 1000 sq. ft. for joints: 15-50 lbs. Per 1000 sq. ft. for texturing.
<b>Setting Type Compound</b> All bedding and topcoats. Allows complete taping and finishing in one day. Recommended for cold weather and slow drying conditions.	25 lb. bags	60 lbs. Per 1000 sq. ft. for joints: 15-50 lbs. Per 1000 sq. ft. for texturing.
<b>Easy Sanding Setting Tape</b> Same use as setting type compound. Applies and sands easier, shrinks less.	22 lb. bags	15-20 lbs. Per 1000 sq. ft.
<b>Ready Mix All Purpose</b> Ready to use for taping and finishing.	12 lb. pails, 30 lb. pails 61.7 lb. pails 48 lb. cartons	60 lbs. Per 700 sq. ft.
<b>Ready Mix Topping</b> Pre-mixed. Finish applications only.	61.7 lb. pails 48 lb. cartons	40 lbs. Per 700 sq. ft.
<b>Lightweight Joint Compound</b> Pre-mixed, ready to use for taping.	4.5 gallons (43 lbs.) cartons and pails	4.5 gallons Per 700 sq. ft.
<b>Tape</b> 2" wide paper tape with spark perforations and skived edges. Reinforces wallboard joints.	60 ft. rolls 250 ft. rolls 500 ft. rolls	400' Per 1000 sq. ft. of gypsum board
<b>Fiberglass Mesh Tape</b> 2" wide, for use in reinforcing glass mat where silicone-treated tile backer is used.	150 ft. rolls	400' Per 1000 sq. ft. of gypsum board

Note: All products ASTM Standard C-475

## Textures

Product	Package Size	Coverage
<b>Wall Texture</b> Decorative finish with either hand tool or spray application.	25 lb. bags	Up to 1000 sq. ft. per 25 lbs. for splatter application; approximately 200 sq. ft. per 25 lbs. for other applications.
<b>Ceiling Textures/Vermiculite</b> For spray application only as a decorative finish for wallboard or concrete ceilings. Not recommended for high-moisture areas such as bathrooms.	40 lb. bags	Varies from 300 to 400 sq. ft. per bag.
<b>Ceiling Textures/Polystyrene</b> For spray application only. Designed for volume application on wallboard or concrete ceilings. Not recommended for high-moisture areas.	32 lb. bags	250 sq. ft. per bag.
<b>Pre-Mixed Ceiling Textures</b> Designed for roll-on application to interior ceilings. Provides a hard, white, textured surface.	2 gallon pails	60 to 120 sq. ft. per 2 gallon pail.

Note: Package size and coverage may vary with manufacturer.

Publisher is not liable for errors or omissions in this book. Always check your local building codes.